


VIRTUOSO

Outdoor




TECHNICAL DETAILS

Light Source	SMD2835	IP Rating	IP165
Colour Temp	2700K/3000K/3500K/4000K/ 5000K/6500K/ Red/Green/Blue	Dimming Options	Non-Dim/Phase-cut Dim/1-10V Dim/DALI Dim/Push Dim/Bluetooth/Remote Control
Mounting	Fixed Surface Mounted	Finish	White
Ballast	Remote	Cuttable Length	35.71mm
Bend Direction	Dual Bend	Warranty	3 Years
Min. Bending Radius	Ø75mm	SDCM	SDCM 3
Tube Dimensions	Ø22mm	Maximum Length	5m with power at single end
Voltage	24VDC	Tail Types	End Feed
Max Power	2x10W/m	Accessories	Mounting Clips
Max. LED tape width	8mm		
CRI	CRi90		
Beam Angle	360°		

VIRTUOSO

Indoor



TECHNICAL DETAILS

Light Source	SMD2216	IP Rating	IP44
Colour Temp	1800K/2400K/2700K/3000K/3500K/4000K/6500K	Dimming Options	Non-Dim/Phase-cut Dim/1-10V Dim/DALI Dim/Push Dim/Bluetooth/Remote Control
Mounting	Fixed Surface Mounted	Finish	White
Ballast	Remote	Cutttable Length	Cutttable at any point for silicone tube; 20mm for LED Strip
Bend Direction	Dual Bend	Warranty	3 Years
Min. Bending Radius	Ø75mm	Maximum Length	5m with power at single end
Tube Dimensions	Ø22mm	Tail Types	End Feed
Voltage	24VDC	Accessories	Mounting Clips
Max Power	2x10W/m		
Max. LED tape width	8mm		
CRI	CR190		
Beam Angle	360°		